

Dado Esagonale Medio




Prodotto di categoria A.

Tolleranze secondo ISO 4759.

Caratteristiche Meccaniche secondo ISO 898/2 (vedi notizie tecniche generali).

Classe: 10
Passo: Fine
CS:
UNI: 5588
DIN: 934
ISO:



Codice	d	passo	s	m	e min.	Kg x 1000	Confezione da
05908100000	M8	1	13	6,5	14,38	5,30	500
05910125000	M10	1,25	17	8	18,9	11,40	500
05912125000	M12	1,25	19	10	21,1	17,20	250
05914150000	M14	1,5	22	11	24,49	24,50	200
05916150000	M16	1,5	24	13	26,75	32,60	200
05918150000	M18	1,5	27	15	30,14	48,20	100
05920150000	M20	1,5	30	16	33,53	62,80	100
05922150000	M22	1,5	32	18	35,72	77,20	100
05924200000	M24	2	36	19	39,98	106,00	100
05927200000	M27	2	41	22	45,63	161,00	50
05930200000	M30	2	46	24	51,28	222,00	50
05933200000	M33	2	50	26	55,8	279,00	50
05936300000	M36	3	55	29	61,31	387,00	40
05939300000	M39	3	60	31	66,96	492,00	25
05942300000	M42	3	65	34	72,61	636,00	25
05945300000	M45	3	70	36	78,26	780,00	25
05948300000	M48	3	75	38	83,91	949,00	10
05952300000	M52	3	80	42	89,56	1180,00	10
05956400000	M56	4	85	45	95,07	1410,00	10
05960400000	M60	4	90	48	100,72	1664,00	10