

Dado Esagonale Alto



Prodotto di categoria A.

Tolleranze secondo ISO 4759.

Caratteristiche Meccaniche secondo ISO 898/2 (vedi notizie tecniche generali).


Classe: 10

UNI: 5587

Passo: Grosso

DIN:

ISO:



Codice	d	s	e min.	m	Kg x 1000	Confezione da
05606000000	M6	10	11,05	6	2,96	2000
05608000000	M8	13	14,38	8	6,53	1000
05610000000	M10	17	18,9	10	14,30	500
05612000000	M12	19	21,1	12	20,30	200
05614000000	M14	22	24,49	14	31,50	200
05616000000	M16	24	26,75	16	40,50	200
05618000000	M18	27	30,14	18	58,20	200
05620000000	M20	30	33,53	20	79,10	100
05622000000	M22	32	35,72	22	95,00	100
05624000000	M24	36	39,98	24	138,00	100
05627000000	M27	41	45,63	27	201,00	50
05630000000	M30	46	51,26	30	286,00	50
05633000000	M33	50	55,8	33	365,00	50
05636000000	M36	55	61,31	36	486,00	50
05639000000	M39	60	66,96	39	633,00	25
05642000000	M42	65	72,61	42	799,00	25
05645000000	M45	70	78,26	45	991,00	25