

# Dado Esagonale Alto



Prodotto di categoria A.

Tolleranze secondo ISO 4759.

Caratteristiche Meccaniche secondo UNI 3740/4 (vedi notizie tecniche generali).


Classe: 8

UNI: 5587

Passo: Fine

DIN:

ISO:



Codice	d	passo	s	m	e min.	Kg x 1000	Confezione da
05108100000	M8	1	13	8	14,38	6,39	2000
05110125000	M10	1,25	17	10	18,9	14,20	1500
05112125000	M12	1,25	19	12	21,1	19,80	200
05114150000	M14	1,5	22	14	24,49	30,80	200
05116150000	M16	1,5	24	16	26,75	39,60	100
05118150000	M18	1,5	27	18	30,14	55,90	200
05120150000	M20	1,5	30	20	33,53	76,20	100
05122150000	M22	1,5	32	22	35,72	91,40	50
05124200000	M24	2	36	24	39,98	133,00	75
05127200000	M27	2	41	27	45,63	195,00	100
05130200000	M30	2	46	30	51,28	274,00	30
05133200000	M33	2	50	33	55,8	350,00	30
05136300000	M36	3	55	36	61,31	474,00	30
05139300000	M39	3	60	39	66,96	612,00	30
05142300000	M42	3	65	42	72,61	782,00	20
05145300000	M45	3	70	45	78,26	980,00	15
05148300000	M48	3	75	48	83,91	1180,00	15
05152300000	M52	3	80	52	89,56	1430,00	10
05156400000	M56	4	85	56	95,07	1730,00	10
05160400000	M60	4	90	60	100,72	2050,00	10